

14AWG 2C SOLID FPLR

Part Number: BC-142SLDFPLR



Listings

Listings c(ETL) us UL Standard 1424 and 444, TIA/EIA-568-C.2, NEC Articles 800 FPLR

Construction

Conductor	14 AWG 2C bare copper
Solid	Yes
Insulation Material	PVC
Nom. Insulation Thickness	0.015"
Insulated Conductor Diameter	0.090"
Number of Conductors	2
Nom. Lay Length	5.5"
Jacket Material	FPLR
Jacket Thickness	0.020"
Nom. Overall Cable Diameter	0.230"
Approximate Cable Weight (lbs./Kft.)	40
Flame Rating	UL 1666 riser flame test
Rip Cord	Yes

Electrical Properties

Nom. DC Resistance per Conductor @ 20°C	2.52 Ohms/Kft. nom.
Capacitance Between Conductors @ 1 KHz	42 pF/ft. nom.
Operating Voltage	300 V RMS max.
Temperature Rating	-20°C to 60 °C

Insulation Color	Black Red
Jacket Color	
Legend (Surface Ink Print)	****/**** comCables 142SLDFPLR 2C 14AWG TYPE CMR/FPLR c(ETL) us 5000838 DC 0315 DEVICE A B C D E F ZONE 0 1 2 3 4 5 6 7 8 9