

# 16AWG 2C (26/30) STRAND FLEX AUDIO CMR

Part Number: BC-16226STR



## Listings

Listings c(ETL)us UL Standard 13 and 42 444, TIR/EIA-568-C.2 NEC Articles 800 CMR

## Construction

Conductor	16 AWG bare copper
Stranding	26/30
Insulation Material	FR-CMR
Nom. Insulation Thickness	0.12"
Insulated Conductor Diameter	0.080"
Number of Conductors	2
Nom. Lay Length	2.4"
Jacket Material	Extra Flexible FR-CMR
Core Wrap	Nonwoven
Jacket Thickness	0.026"
Nom. Overall Cable Diameter	0.212"
Approximate Cable Weight (lbs./Kft.)	29 lbs
Flame Rating	UL 1581 vertical tray flame test
Rip Cord	No

## Electrical Properties

Nom. DC Resistance per Conductor @ 20°C	4.02 Ohms/Kft. nom.
Capacitance Between Conductors @ 1 KHz	30 pF/ft. nom.
Operating Voltage	300 V RMS max.
Temperature Rating	-20°C to 60 °C

Insulation Color	Red   Black
Jacket Color	
Legend (Surface Ink Print)	****/**** comCables 16226STR OFC "FLEX AUDIO" 16AWG 2C TYPE CMR c(ETL) us 5000838 DC 0315 DEVICE A B C D E F ZONE 0 1 2 3 4 5 6 7 8 9