

# 16AWG 4C (26/30) STRAND FLEX AUDIO CMR

Part Number: BC-16426STR



## Listings

Listings c(ETL)us UL Standard 13 and 42 444, TIA /EIA-568-C.2 NEC Articles 800 CMR

## Construction

Conductor	16AWG bare copper
Stranding	26/30
Insulation Material	FR-PVC
Nom. Insulation Thickness	0.12"
Insulated Conductor Diameter	0.080"
Number of Conductors	4
Nom. Lay Length	5.1"
Jacket Material	CMR
Core Wrap	Nonwoven
Jacket Thickness	0.023"
Nom. Overall Cable Diameter	0.24"
Approximate Cable Weight (lbs./Kft.)	50
Flame Rating	UL 1581 vertical tray flame test

## Electrical Properties

Nom. DC Resistance per Conductor @ 20°C	4.02 Ohms/Kft. nom.
Capacitance Between Conductors @ 1 KHz	30 pF/ft. nom.
Operating Voltage	300 V RMS max.
Temperature Rating	-20°C to 60 °C

Insulation Color	Black   Red   White   Green
Jacket Color	
Legend (Surface Ink Print)	****/**** comCables 16426STR OFC "FLEX AUDIO" 16AWG 4C TYPE CMR c(ETL) us 5000838 DC 0315 DEVICE A B C D E F ZONE 0 1 2 3 4 5 6 7 8 9