

# 16AWG 4C SOLID FPLR

Part Number: BC-164SLDFPLR



## Listings

Listings Type FPLR c(ETL)us 5000838

## Construction

Conductor	16 AWG 4C bare copper
Solid	Yes
Insulation Material	PVC
Nom. Insulation Thickness	0.10"
Insulated Conductor Diameter	0.070"
Nom. Lay Length	6.0"
Jacket Material	FPLR
Jacket Thickness	0.020"
Nom. Overall Cable Diameter	0.225"
Approximate Cable Weight (lbs./Kft.)	55
Flame Rating	UL 1581 vertical tray flame test
Rip Cord	Yes

## Electrical Properties

Nom. DC Resistance per Conductor @ 20°C	4.02 Ohms/Kft. nom.
Capacitance Between Conductors @ 1 KHz	40 pF/ft. nom.
Operating Voltage	300 V RMS max.
Temperature Rating	-20°C to 60 °C

Insulation Color	Black   Red   Blue   Yellow
Jacket Color	
Legend (Surface Ink Print)	****/**** comCables 164SLDFPLR 16AWG 4C TYPE CMR/FPLR c(ETL) us 5000838 DC 0315 DEVICE A B C D E F ZONE 0 1 2 3 4 5 6 7 8 9