

# 18AWG 6C (7/26) STRAND CMR

Part Number: BC-186STR



## Listings

Listings Type FPLR c(ETL)us 5000838

## Construction

Conductor	18AWG bare copper
Stranding	7/26
Insulation Material	PVC
Nom. Insulation Thickness	0.010"
Insulated Conductor Diameter	0.068"
Number of Conductors	6
Nom. Lay Length	5.5"
Jacket Material	PVC
Jacket Thickness	0.020"
Nom. Overall Cable Diameter	0.235"
Approximate Cable Weight (lbs./Kft.)	47
Flame Rating	UL 1581 vertical tray flame test
Rip Cord	Yes

## Electrical Properties

Nom. DC Resistance per Conductor @ 20°C	6.43 Ohms/Kft. nom.
Capacitance Between Conductors @ 1 KHz	35 pF/ft. nom.
Operating Voltage	300 V RMS max.
Temperature Rating	-20°C to 60 °C

Insulation Color	Black   Red   White   Green   Brown   Blue
Jacket Color	
Legend (Surface Ink Print)	****/**** comCables 186STR 18AWG 6C TYPE CMR c(ETL)us 5000838 DC 1014 DEVICE A B C D E F ZONE 0 1 2 3 4 5 6 7 8 9