

22AWG 4C STRAND CMP

Part Number: BC-224STRCMP



Listings

Listings c(ETL)us UL Standard 13 and 42 444, TIA/EIA-568-C.2 NEC Articles 800 CMR

Construction

Conductor	22 AWG bare copper
Stranding	7/30
Insulation Material	Low Smoke PVC
Nom. Insulation Thickness	0.008"
Insulated Conductor Diameter	0.046"
Number of Conductors	4
Nom. Lay Length	4.5"
Jacket Material	Low Smoke PVC
Jacket Thickness	0.015"
Nom. Overall Cable Diameter	0.140"
Approximate Cable Weight (lbs./Kft.)	15
Flame Rating	UL 910 Steiner Tunnel Smoke Flame Test
Rip Cord	Yes

Electrical Properties

Nom. DC Resistance per Conductor @ 20°C	16.19 Ohms/Kft. nom.
Capacitance Between Conductors @ 1 KHz	25 pF/ft. nom.
Operating Voltage	300 V RMS max.
Temperature Rating	-20°C to 75 °C

Insulation Color	Black Red White Green
Jacket Color	Natural
Legend (Surface Ink Print)	****/**** comCables 224STR 22AWG 4CTYPE CMP c(ETL)us 5000838 DC 1014 DEVICE A B C D E F ZONE 0 1 2 3 4 5 6 7 8 9