

# 22AWG 6C STRANDED SHIELDED CMP

Part Number: BC-226STRCMR



## Listings

Listings c(ETL)us UL Standard 13 and 42 444, TIA/EIA-568-C.2 NEC Articles 800 CMR

## Construction

Conductor	22 AWG bare copper
Stranding	7/30
Insulation Material	Low Smoke PVC
Nom. Insulation Thickness	0.008"
Insulated Conductor Diameter	0.046"
Number of Conductors	6
Nom. Lay Length	5.0"
Jacket Material	Low Smoke PVC
Jacket Thickness	0.015"
Nom. Overall Cable Diameter	0.175"
Approximate Cable Weight (lbs./Kft.)	26
Flame Rating	UL 910 Steiner Tunnel Smoke and Flame Test
Rip Cord	No

## Electrical Properties

Nom. DC Resistance per Conductor @ 20°C	16.19 Ohms/Kft. nom.
Capacitance Between Conductors @ 1 KHz	35 pF/ft. nom.
Operating Voltage	300 V RMS max.
Temperature Rating	-20°C to 75 °C

Insulation Color	Black   Red   White   Green   Brown   Blue
Jacket Color	Natural
Legend (Surface Ink Print)	****/**** comCables 226STR 22AWG 6C TYPE CMR c(ETL)us
5000838 DC 1014	DEVICE A B C D E F ZONE 0 1 2 3 4 5 6 7 8 9