

# RG6 QUAD SHIELD 18AWG SOLID CCS CMR

Part Number: BC-RG6QUAD



## Listings

Listings c(ETL)us UL Standard 13 and UL 444, TIA/EIA-568-C.2 NEC Articles 800

## Constructions

Conductor	18 AWG Solid CCS
Dielectric	Foamed PE
Nom. Dielectric Wall Thickness	0.070"
Nom. Dielectric Diameter	0.180"
Shield	Bonded Polyester/Aluminum Tape and 60% Aluminum Braid
Nom. Shield Diameter	0.249"
Jacket Material	PVC
Jacket Thickness	0.029"
Nom. Overall Cable Diameter	0.295"
Approximate Cable Weight (lbs./Kft.)	38lbs
Flame Rating	UL 1581 Vertical Tray Flame Test
Rip Cord	No

## Electrical Properties

Nom. DC Resistance per Conductor @ 20°C	10.2
Capacitance Between Conductors @ 1 KHz	117.3 pF/ft
Operating Voltage	
Temperature Rating	75° C
Min. Velocity of Propagation	78%
Frequency Rating	max 3000 MHz
Insulation Color	White
Jacket Color	Black
Legend (Surface Ink Print)	**/**FT comCables RG6QUAD RG6 QUAD SHIELD CATV c(ETL)us 5000838 CMR 3.0GHz UV Protected DC 1014 DEVICE A B C D E F ZONE 0 1 2 3 4 5 6 7 8 9